

LUMB MONO BLOCK UNITS

Air Cooled Type Units For Walk-In Cold Room

- Wall Mounted Type
- Roof Top Mounted Type



LUTHER-BACH HEAT EXCHANGER CO.,LTD

Wall Mounted Type

Model	Refrigerant	Voltage	Cooling Capacity W	Power KW	Current A	Suggested Volume		Size L*W*H mm
						Min/m ³	Max/m ³	
Medium & High Temp. Application (-5°C to +5°C)								
LUMB-WHA008J	R404A	220V/1Ph/50Hz	1180	0.9	4.3	6	9	825*450*769
LUMB-WHA010J	R404A	220V/1Ph/50Hz	1550	1.1	4.9	8	14	825*450*769
LUMB-WHA015J	R404A	220V/1Ph/50Hz	2160	1.4	6.8	13	26	1045*530*845
LUMB-WHA020J	R404A	220V/1Ph/50Hz	2740	1.8	9.9	23	31	1045*530*845
LUMB-WHA025J	R404A	220V/1Ph/50Hz	3920	2.4	8.8	28	52	1045*620*845
LUMB-WHA030J	R404A	220V/1Ph/50Hz	4785	2.9	13.9	30	60	1200*800*970
LUMB-WHA035J	R404A	220V/1Ph/50Hz	5560	3.4	12	52	87	1200*800*970
LUMB-WHA035D	R404A	380V/3PH/50Hz	5360	3.2	6.5	52	87	1200*800*970
LUMB-WHA040D	R404A	380V/3PH/50Hz	6135	3.6	7.8	65	120	1200*800*970
Low Temp. Application (-20°C to -10°C)								
LUMB-WLA010J	R404A	220V/1Ph/50Hz	1240	1.1	6.6	4	9	825*450*769
LUMB-WLA012J	R404A	220V/1Ph/50Hz	1421	1.1	7.3	6	12	825*450*769
LUMB-WLA015J	R404A	220V/1Ph/50Hz	1600	1.5	9.9	7	14	1045*530*845
LUMB-WLA020J	R404A	220V/1Ph/50Hz	2240	1.9	7.7	11	23	1045*530*845
LUMB-WLA025J	R404A	220V/1Ph/50Hz	2785	2.2	11.8	16	30	1045*620*845
LUMB-WLA030J	R404A	220V/1Ph/50Hz	3305	2.7	10.9	17	38	1045*620*845
LUMB-WLA030D	R404A	380V/3PH/50Hz	3050	2.5	5.9	16	36	1045*620*845
LUMB-WLA040D	R404A	380V/3PH/50Hz	3680	2.8	7.9	20	48	1200*800*970
LUMB-WLA050D	R404A	380V/3PH/50Hz	6250	4.4	9.6	52	95	1200*800*970

Roof Top Mounted Type

Model	Refrigerant	Voltage	Cooling Capacity W	Power KW	Current A	Suggested Volume		Size L*W*H mm
						Min/m ³	Max/m ³	
Medium & High Temp. Application (-5°C to +5°C)								
LUMB-RHA008J	R404A	220V/1Ph/50Hz	1180	0.6	3.5	6	9	710*620*510
LUMB-RHA010J	R404A	220V/1Ph/50Hz	1550	0.9	4.6	8	14	1320*720*560
LUMB-RHA015J	R404A	220V/1Ph/50Hz	2160	1.1	6	13	26	1320*720*560
LUMB-RHA020J	R404A	220V/1Ph/50Hz	2740	1.5	8	23	31	1320*720*560
LUMB-RHA025J	R404A	220V/1Ph/50Hz	3920	2.1	10.9	28	52	1320*720*560
LUMB-RHA030J	R404A	220V/1Ph/50Hz	4785	2.4	13.9	30	60	1320*1070*600
LUMB-RHA035J	R404A	220V/1Ph/50Hz	5560	3	15.4	52	87	1320*1070*600
LUMB-RHA035D	R404A	380V/3PH/50Hz	5360	2.7	5.6	52	87	1320*1070*600
LUMB-RHA040D	R404A	380V/3PH/50Hz	6135	3.2	7.5	65	120	1320*1070*600
Low Temp. Application (-20°C to -10°C)								
LUMB-RLA010J	R404A	220V/1Ph/50Hz	1240	0.8	6	4	9	710*620*510
LUMB-RLA012J	R404A	220V/1Ph/50Hz	1421	0.9	6.7	4	9	710*620*510
LUMB-RLA015J	R404A	220V/1Ph/50Hz	1600	1.4	7.4	6	12	1320*720*560
LUMB-RLA020J	R404A	220V/1Ph/50Hz	2240	1.9	10.2	7	14	1320*720*560
LUMB-RLA025J	R404A	220V/1Ph/50Hz	2785	2.1	11.8	11	23	1320*720*560
LUMB-RLA030J	R404A	220V/1Ph/50Hz	3305	2.5	13.6	16	30	1320*720*560
LUMB-RLA030D	R404A	380V/3PH/50Hz	3050	2.4	6.2	15	29	1320*720*560
LUMB-RLA040D	R404A	380V/3PH/50Hz	3680	2.7	8.1	20	48	1320*1070*600
LUMB-RLA050D	R404A	380V/3PH/50Hz	6250	4.3	8.7	52	95	1320*1070*600

Note: 220V/1Ph/60Hz & 220V/3Ph/60Hz also available

LUTHER-BACH HEAT EXCHANGER CO.,LTD

路德巴赫换热器工业(中国)有限公司

Add: Shengzhou City, Shaoxing City, Zhejiang Province, China

Tel: +86-574-87683926

Fax: +86-574-87683927

Mobile: +86 183 6823 8236

+86 138 5836 9959

Email: lb@luther-bach.com

lb18@luther-bach.com

Web: www.luther-bach.com

